









Foto	Descripcion	Medida	
ART. NO.	PHOTO	DESCRIPTION	Potencia
7400		<p>1.CE,CCC, RoHS certification 2.Voltage: 90V-270V, power factor >0.99 3. Main frequency: 230KHZ, input frequency:50Hz 4.Operating temp.: -35 to+50□ 5.Color temperature:2100K-6400K 6.Quality: 5 years guaranteed,100000 hours lifespa 7.Ballast is protected from short-circuit, open-circuit, etc. 8.Size:D55.5*H41CM</p>	100W:
7401		<p>1. CE,CCC,RoHS certification 2.Voltage: 90V-270V, power factor >0.99 3. Main frequency: 230KHZ, input frequency:50Hz 4.Operating temp.: -35 to+50□ 5.Color temperature:2700K-6400K 6.Quality: 5 years guaranteed,100000 hours lifespan 7.Ballast is protected from short-circuit, open-circuit, etc. 8.Size: L54*W22.5*H14CM</p>	200W: 300W:
7402		<p>1. CE,CCC, RoHS certification 2.Voltage: 90V-270V, power factor >0.99 3. Main frequency: 230KHZ, input frequency:50Hz 4.Operating temp.: -35 to+50□ 5.Color temperature:2700K-6400K 6. 5 years guaranteed,100000 hours lifespan 7.Ballast is protected from short-circuit, open-circuit, etc. 8.Size: L59*W38*H33CM</p>	150W:
7403		<p>1. CE,CCC, RoHS certification 2.Voltage: 90V-270V, power factor >0.99 3. Main frequency: 230KHZ, input frequency:50Hz 4.Operating temp.: -35 to+50□ 5.Color temperature:2700K-6400K 6. 5 years guaranteed,100000 hours lifespan 7.Ballast is protected from short-circuit, open-circuit, etc. 8.Size: L41*W40.5*H13.5CM</p>	100W:
7404		<p>1. CE,CCC, RoHS certification 2.Voltage: 90V-270V, power factor >0.99 3. Main frequency: 230KHZ, input frequency:50Hz 4.Operating temp.: -35 to+50□ 5.Color temperature:2700K-6400K 6. 5 years guaranteed,100000 hours lifespai 7.Ballast is protected from short-circuit, open-circuit, etc. 8.Size: L72*W48*H48CM</p>	100W
7405		<p>1. CE,CCC, RoHS certification 2.Voltage: 90V-270V, power factor >0.99 3. Main frequency: 230KHZ, input frequency:50Hz 4.Operating temp.: -35 to+50□ 5.Color temperature:2700K-6400K 6. 5 years guaranteed,100000 hours lifespan 7.Ballast is protected from short-circuit, open-circuit, etc. 8.Size: L28*W21*H16CM</p>	40W:
7406		<p>1. CE,CCC, RoHS certification 2.Voltage: 90V-270V, power factor >0.99 3. Main frequency: 230KHZ, input frequency:50Hz 4.Operating temp.: -35 to+50□ 5.Color rendering:2100K-6400K 6.Quality: 5 years guaranteed,100000 hours lifespan 7.Ballast is protected from short-circuit, open-circuit, etc. 8.Size: D25.5*H15 CM</p>	40W:
7407		<p>1. CE,CCC, RoHS certification 2.Voltage: 90V-270V, power factor >0.99 3. Main frequency: 230KHZ, input frequency:50Hz 4.Operating temp.: -35 to+50□ 5.Color temperature:2100K-6400K 6.Quality: 5 years guaranteed 7.Ballast is protected from short-circuit, open-circuit, etc.</p>	100W:
7408		<p>1. CE,CCC, RoHS certification 2.Voltage: 90V-270V, power factor >0.99 3. Main frequency: 230KHZ, input frequency:50Hz 4.Operating temp.: -35 to+50□ 5.Color temperature:2100K-6400K 6.Quality: 5 years guaranteed 7.Ballast is protected from short-circuit, open-circuit, etc.</p>	100W:
7409		<p>Model: RZHL801 1. CE,CCC, RoHS certification 2.Voltage: 90V-270V, power factor >0.99 3. Main frequency: 230KHZ, input frequency:50Hz 4.Operating temp.: -35 to+50□ 5.Color temperature:2100K-6400K 6.Quality: 3 years guaranteed,lifespan 60,000 hours 7.Ballast is protected from short-circuit, open-circuit, etc.</p>	80W: