








**200mm de diametro**

Codigo	Product Image	Main Parameter
9020	<b>200 mm rojo</b> 	Input Voltage AC: 110V-120V/ 220V-240V/24VDC, 50/60HZ Power Consumption 8W Wavelength (nm) 620-625 Intensity (cd) >= 400 cd Body Material PC Dimension Φ200mmx100mm Packing 20Units/CTN Weight N.W: 0.7KG/PCS, G.W:15KG
	<b>200 mm Amarillo</b> 	Input Voltage AC: 110V-120V/ 220V-240V, 50/60HZ Power Consumption 8W Wavelength (nm) 590-595 Intensity (cd) >= 400 cd Body Material PC Dimension 200mmx100mm Packing 20Units/CTN Weight N.W: 0.7KG/PCS, G.W:15KG
	<b>200 mm Verde</b> 	Input Voltage AC: 110V-120V/ 220V-240V, 50/60HZ Power Consumption 8W Wavelength (nm) 500-505 Intensity (cd) >= 400 cd Body Material PC Dimension 200mmx100mm Packing 20Units/CTN Weight N.W: 0.7KG/PCS, G.W:15KG


**300mm de diametro**

Precios	Product Image	Main Parameter
9023	<b>300 mm Rojo</b> 	Input Voltage AC: 110V-120V/ 220V-240V, 50/60HZ Power Consumption 10W Wavelength (nm) 620-625 Intensity (cd) >= 500 cd Body Material PC Dimension 300mmx80mm Packing 10Units/CTN Weight N.W: 1.2KG/PCS, G.W:11KG
	<b>300 mm Amarillo</b> 	Input Voltage AC: 110V-120V/ 220V-240V, 50/60HZ Power Consumption 10W Wavelength (nm) 590-595 Intensity (cd) >= 500 cd Body Material PC Dimension 300mmx80mm Packing 10Units/CTN Weight N.W: 1.2KG/PCS, G.W:11KG
	<b>300 mm Verde</b> 	Input Voltage AC: 110V-120V/ 220V-240V, 50/60HZ Power Consumption 10W Wavelength (nm) 500-505 Intensity (cd) >= 500 cd Body Material PC Dimension 300mmx80mm Packing 10Units/CTN Weight N.W: 1.2KG/PCS, G.W:11KG


9026

Product Image	Main Parameter
	Input Voltage AC: 110V-120V/ 220V-240V, 50/60HZ
	Power Consumption R Ball =< 8W, Y Ball =< 8W, G Ball =< 9W
	Wavelength (nm) R: 625±5, Y: 590±5, G: 505±2
	Intensity (cd) >= 400 cd
	Housing Material PC Only
	Dimension 750x250x160mm
	Packing: 2sets/Carton, 770 x 370 x 270 mm, 18.5 kgs


9027

Product Image	Main Parameter
 <p>Semaforo Completo</p>	Input Voltage AC: 110V-120V/ 220V-240V, 50/60HZ
	Power Consumption R Ball =< 12W, Y Ball =< 12W, G Ball =< 13W
	Wavelength (nm) R: 625±5, Y: 590±5, G: 505±2
	Intensity (cd) >= 500 cd
	Housing Material Aluminum/PC
	Dimension 1110x370x160mm
Packing: 2sets/carton, 1150 x 340 x 430 mm, G.W: 34.0 kgs	

9028


Product Image	Main Parameter
 <p>300 mm Rojo Peaton</p>	Input Voltage AC: 110V-120V/ 220V-240V, 50/60HZ
	Power Consumption 7W
	Wavelength (nm) 620-625
	Intensity (cd) >= 210cd
	Body Material PC
	Dimension 300mmx80mm
	Packing 10Units/CTN
Weight N.W: 1.2KG/PCS, G.W:11KG	

9029

Product Image	Main Parameter
 <p>300 mm Verde Peaton</p>	Input Voltage AC: 110V-120V/ 220V-240V, 50/60HZ
	Power Consumption 7W
	Wavelength (nm) 500-505
	Intensity (cd) >= 280cd
	Body Material PC
	Dimension 300mmx80mm
	Packing 10Units/CTN
Weight N.W: 1.2KG/PCS, G.W:11KG	

9030

9031

Product Image	Main Parameter
	Model No. DX-FX300-3-ZGSM-3-JG
	Input Voltage AC: 110V-120V/ 220V-240V, 50/60HZ
	Power Consumption 8W
	Wavelength (nm) 500-505
	Intensity (cd) >= 300cd
	Body Material PC
	Dimension 300mmx80mm
	Packing 10Units/CTN
Weight N.W: 1.2KG/PCS, G.W:11KG	